

TITAN GT1 LONGLIFE III SAE 0W-30

Premium engine oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for VW vehicles with exhaust after treatment and turbocharger. Good cold starting, lower oil consumption and minimized exhaust emissions.

Description

Technological developments in the automotive industry have resulted in engines which are showing less fuel consumption, reduced exhaust gas emissions and extended maintenance intervals. The realization of these benefits requires extremely high-performing engine oils which operate throughout oil change intervals of up to 50,000 km or two years. TITAN GT1 LONGLIFE III SAE 0W-30 was developed for VW engines and formulated for outstanding Fuel Economy characteristics. Now nearly all engines, irrespectively of their make or design can be filled with this oil. Particularly, diesel engines equipped with particulate filters, which last significantly longer with this engine oil.

Application

TITAN GT1 LONGLIFE III SAE 0W-30 is specially developed for VW vehicles. It can be used for extended drain intervals as well as for standard drain intervals. Moreover, TITAN GT1 LONGLIFE III SAE 0W-30 can be applied for service of older VW vehicles as well.

TITAN GT1 LONGLIFE III SAE 0W-30 is miscible and compatible with conventional branded engine oils. However, mixing with other engine oils should be avoided in order to fully utilize the product's benefits. A complete oil change is recommended when changing to TITAN GT1 LONGLIFE III SAE 0W-30. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages/Benefits

- Can be used in all VW gasoline and diesel engines, including all further VW approvals
- Outstanding wear protection
- Can be used in vehicles with extended oil drain intervals of 50,000 km or two years
- Reduces ash formation in particulate filters and reduces fuel consumption
- Increases the lifetime of particulate filters
- Can be used for older VW vehicles as well (without long drain interval)
- Protects three-way catalysts of poisoning

Specifications

- ACEA C3

Approvals

- VW 504 00/507 00

FUCHS Recommendations

- -

PI60780e, PMA, 09.07.2019, Page 1

TYPICAL CHARACTERISTICS

Density at 15 °C	DIN 51757	0.843 g/ml
SAE grade	SAE J300	0W-30
Kinematic Viscosity at 40°C	DIN 51562-1	60.6 mm²/s
Kinematic Viscosity at 100°C	DIN 51562-1	12.1 mm²/s
Viscosity index	DIN ISO 2909	203
HTHS	CEC L-036-90	≥ 3.5 mPa*s
Pour Point	DIN ISO 3016	-51 °C
Sulphated ash	ASTM D874	≤ 1.5 % m/m
Product dyeing	DIN 10964	none

PI60780e, PMA, 09.07.2019, Page 2